Blackline S218⁺

Dual driver, vented sub-bass system

features

- Dual direct radiating 18" (460mm) drivers
- ▶ High temperature 4" (100mm) voice coil
- Fitted with handles and castors
- Five year limited warranty


applications


- Large scale club performance
- Large club installs

The powerful Blackline S218⁺ sub-bass system has been designed to be used with large scale Blackline F12⁺ and F15⁺ systems to extend and increase the total low frequency output power. It can also be used as the low frequency section of a bi-amped or tri-amped H3⁺ system. The S218⁺ provides good bass punch with extended sub-bass output from two new, long-excursion, 18" (460mm)/4" (100mm) voice coil drivers with water resistant cones and triple roll surrounds.

The $S218^+$ must be electronically crossed over with the $M3^+$, DXI or equivalent Electronic Controller.

overall dimensions





S218+



technical specifications

TYPE	Dual-driver, vented sub-bass system
FREQUENCY RESPONSE (I)	$35Hz-150Hz \pm 3dB$
	-10dB @ 28Hz
DRIVERS	2 x 18" (460mm)/4" (100mm) voice coil LF drivers
RATED POWER (2)	1500W AES, 6000W peak
RECOMMENDED AMPLIFIER	1000W-2500W into 4 ohms
SENSITIVITY (3)	105dB (half space)
MAXIMUM SPL (4)	136.5dB continuous, 142.5dB peak (half space)
NOMINAL IMPEDANCE	4 ohms
DISPERSION (-6dB)	
CROSSOVER	80-150Hz active
ENCLOSURE	320 litre, multi-laminate birch ply
FINISH	Textured black paint
PROTECTIVE GRILLE	Black perforated steel
CONNECTORS	2 x Neutrik NL4
PIN CONNECTIONS	LF+,-: I+,I- and 2+,2-
FITTINGS	4 x 4" (100mm) castors
	6 x pocket handles
	2 x lid clips
DIMENSIONS (inc wheels)	(W) 561mm x (H) 1066mm x (D) 780mm (911mm)
	(W) 22.1 ins x (H) 42ins x (D) 30.7 ins (35.9 ins)
WEIGHT	87kg (191.5lbs)

Century Point, Halifax Road, Cressex Business Park,
High Wycombe, Buckinghamshire HP12 3SL, England.
Telephone: +44 (0)1494 53311 Facsimile: +44 (0)1494 438669
E-mail: info@martin-audio.com
All information is Copyright © 2007 Martin Audio Ltd.

